

Engine	Yanmar 4TNV98T-ZSLY
Gross Power	56.5kW (76 hp) @ 2,200 rpm
Net Power	54.3kW (72.8 hp) @ 2,200 rpm
Maximum Digging Depth	4,150 mm
Standard Bucket Capacity	0.32 m ³
Operating Weight	7,800 kg

CLG908D Excavator



TOUGH WORLD. TOUGH EQUIPMENT.

ENGINE

Emission Regulation	Stage III A
Make	Yanmar
Model	4TNV98T-ZSLY
Gross Power	56.5 kW (76 hp) @ 2,200 rpm
Net Power	54.3 kW (72.8 hp) @ 2,200 rpm
Peak Torque	277 N • m @ 1,650 rpm
Number of Cylinders	4
Displacement	3.3 L

TRACK DRIVE

Maximum Travel Speed	4.2 km/h
Gradeability	70 %
Drawbar Pull	56 kN

UNDERCARRIAGE

Shoe Width	450 mm
Number of Shoes per Side	39
Number of Bottom Rollers per Side	6
Number of Upper Rollers per Side	1

HYDRAULIC SYSTEM

Main Pumps Total Flow	198 L/min
Relief Pressure, main	27.4 MPa

REFERENCE ARM

Arm Length	1,650 mm
Arm Breakout Force, normal, ISO	40.1 kN

WORKING RANGES

Maximum Dig Depth	4,150 mm
Reach at Ground Level	6,225 mm
Depth of 8' Level Bottom	3,785 mm
Maximum Dig Height	7,150 mm
Dump Height	5,080 mm
Maximum Dig Depth of Vertical Wall	3,230 mm

BUCKET PERFORMANCE

Standard Bucket Heaped Capacity (Referenced)	0.32 m ³
Minimum Heaped Capacity of Bucket Options	0.14 m ³
Maximum Heaped Capacity of Bucket Options	0.4 m ³
Bucket Breakout Force, normal, ISO	61 kN

SERVICE CAPACITIES



Fuel Tank	175 L
Engine Oil	7 L
Cooling System	15 L
Hydraulic Reservoir	60 L
Hydraulic System Total	113 L

SWINGSYSTEM

Swing Speed	10 rpm
-------------	--------

Bucket: SAE 0.32 m ³ Boom: 3,710 mm Arm: 1,650 mm Shoes: 450 mm									
Lift Point Height									
		2 m		3 m		4 m		5 m	
5 m	kg			※1,471	※1,471				
4 m	kg			※1,590	※1,590	※1,545	※1,545		
3 m	kg	※2,635	※2,635	※1,995	※1,995	※1,713	1,577		
2 m	kg	※4,320	※4,320	※2,575	2,329	※1,972	1,493	※1,583	1,087
1 m	kg	※5,188	※4,148	※3,070	2,169	※2,221	1,413	※1,685	1,048
0	kg	※5,091	4,094	※3,285	2,081	※2,367	1,357	※1,796	1,006
-1 m	kg	※4,737	4,096	※3,221	2,052	※2,349	1,332	※1,852	976
-2 m	kg	※4,099	※4,099	※2,879	2,067	※2,081	1,344		

- ※ Indicates the load is limited by hydraulic capacity rather than tipping capacity.
- The above rated loads are in compliance with ISO 10567 hydraulic excavator lift capacity rating standard. They do not exceed 87% of hydraulic lifting capacity or 75% tipping load.
- Ratings at bucket lift hook, the dozer blade is up.



Unit: mm

Guangxi Liugong Machinery Co., Ltd.

No. 1 Liutai Road, Liuzhou, Guangxi 545007, PR China
T: +86 772 3886124 E: overseas@liugong.com
www.liugong.com

04/2014 Designed by LiuGong